

LV0114 FLOOD WORK LAMP

FEATURES:

- Flood Beam Pattern
- 9-32 Volt DC
- 1 x 10 Watt CREE LED
- Protected against RFI/EMC interference
- Over/Under Voltage Protection
- Tempered Glass Lens
- Die-Cast Aluminium Housing
- Stainless Steel Mounting Bracket and Hardware
- Working Environment -40°C to +60°C
- Sealed to IP67
- Pre Wired with 30cm Cable
- Life Time 30,000 hours
- Current Draw: 0.9 Amp @ 12V and 0.4 Amp @ 24V
- 900 Lumen Output
- 40° Beam Pattern
- Dimensions: 66 x 66 x 65mm



LV0115 FLOOD WORK LAMP

FEATURES:

- Flood Beam Pattern
- 9-32 Volt DC
- 2 x 10 Watt CREE LED
- Protected against RFI/EMC interference
- Over/Under Voltage Protection
- PMMA(Polycarbonate) Lens
- Die-Cast Aluminium Housing
- Stainless Steel Mounting Bracket and Hardware
- Working Environment -40°C to +60°C
- Sealed to IP67
- Pre Wired with 30cm Cable
- Life Time 30,000 hours
- Current Draw: 1.7 Amp @ 12V and 0.85 Amp @ 24V
- 1800 Lumen Output
- 90° Beam Pattern
- Dimensions: 110 x 114 x 60mm



LV0116 FLOOD WORK LAMP

FEATURES:

- Flood Beam Pattern
- 9-32 Volt DC
- 30 x 1 Watt LED's
- Reverse Polarity Protection
- PMMA(Polycarbonate) Lens
- Die-Cast Aluminium Housing
- Stainless Steel Mounting Bracket and Hardware
- Working Environment -40°C to +60°C
- Sealed to IP67
- Pre Wired with 30cm Cable
- Life Time 30,000 hours
- Current Draw: 2.7 Amp @ 12V and 1.3 Amp @ 24V
- 2100 Lumen Output
- 160° Beam Pattern
- Dimensions: 126 x 126 x 85mm



LV0117 FLOOD WORK LAMP

FEATURES:

- Flood Beam Pattern
- 9-32 Volt DC
- 4 x 10 Watt CREE LED
- Protected against RFI/EMC interference
- Over/Under Voltage Protection
- PMMA (Polycarbonate) Lens
- Die-Cast Aluminium Housing
- Stainless Steel Mounting Bracket and Hardware
- Working Environment -40°C to +60°C
- Sealed to IP67
- Pre Wired with 30cm Cable
- Life Time 30,000 hours
- Current Draw: 3 Amp @ 12V and 1.5 Amp @ 24V
- 3600 Lumen Output
- 45° Beam Pattern
- Dimensions: 110 x 110 x 72mm



LV0120 FLOOD WORK LAMP

FEATURES:

- Flood Beam Pattern
- 9-32 Volt DC
- Integrated 55W Ballast
- H11 55W 6000K HID Globe
- Protected against RFI/EMC interference
- Tempered Glass Lens
- Die-Cast Aluminium Housing
- Stainless Steel Mounting Bracket and Hardware
- Working Environment -40°C to +105°C
- Sealed to IP67
- Pre Wired with 30cm Cable
- Current Draw: 4.5 Amp @ 12V and 2.2 Amp @ 24V
- 4200 Lumen Output
- Dimensions: 150 x 130 x 160mm



LV0121 FLOOD WORK LAMP

FEATURES:

- Flood Beam Pattern
- 9-32 Volt DC
- Integrated 35W Ballast
- H3 35W 6000K HID Globe
- Protected against RFI/EMC interference
- Tempered Glass Lens
- High Impact Plastic Housing
- Moulded Nylon Housing
- Stainless Steel Mounting Bracket and Hardware
- Working Environment -40°C to +105°C
- Sealed to IP67
- Pre Wired with 30cm Cable
- Current Draw: 2.9 Amp @ 12V and 1.4 Amp @ 24V
- 3200 Lumen Output
- Dimensions: 110 x 110 x 130mm



LV0122 FLOOD WORK LAMP

FEATURES:

- Flood Beam Pattern
- 9-32 Volt DC
- Integrated 55W Ballast
- H1 55W 6000K HID Globe
- Protected against RFI/EMC interference
- Tempered Glass Lens
- Moulded Nylon Housing
- Stainless Steel Mounting Bracket and Hardware
- Working Environment -40°C to +105°C
- Sealed to IP67
- Pre Wired with 30cm Cable
- Current Draw: 4.5 Amp @ 12V and 2.2 Amp @ 24V
- 4200 Lumen Output
- Dimensions: 145 x 185 x 155mm

